



SIMATIC ET 200SP, Digital output module, DQ 8x 24V DC/0.5A Standard, Source output (PNP,P-switching) Packing unit: 1 piece, fits to BU-type A0, Colour Code CC02, substitute value output, module diagnostics for: short-circuit to L+ and ground, wire break, supply voltage

General information	
Product type designation	DQ 8x24VDC/0.5A ST
HW functional status	From FS02
Firmware version	V0.0
• FW update possible	No
usable BaseUnits	BU type A0
Color code for module-specific color identification plate	CC02
Product function	
• I&M data	Yes; I&M0 to I&M3
• Isochronous mode	No
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	V14
• STEP 7 configurable/integrated from version	V5.5 SP3 or higher
• PCS 7 configurable/integrated from version	V8.1 SP1
• PROFIBUS from GSD version/GSD revision	One GSD file each, Revision 3 and 5 and higher
• PROFINET from GSD version/GSD revision	GSDML V2.3
Operating mode	
• DQ	Yes
• DQ with energy-saving function	No
• PWM	No
• Oversampling	No
• MSO	No
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption, max.	35 mA; without load
output voltage / header	
Rated value (DC)	24 V
Power loss	
Power loss, typ.	1 W
Address area	
Address space per module	
• Address space per module, max.	1 byte; + 1 byte for QI information
Hardware configuration	
Automatic encoding	Yes
• Mechanical coding element	Yes
• Type of mechanical coding element	Type A

<b>Selection of BaseUnit for connection variants</b>	
<ul style="list-style-type: none"> <li>• 1-wire connection</li> <li>• 2-wire connection</li> <li>• 3-wire connection</li> <li>• 4-wire connection</li> </ul>	BU type A0 BU type A0 BU type A0 with AUX terminals or potential distributor module BU type A0 + Potential distributor module
<b>Digital outputs</b>	
Type of digital output	Source output (PNP, current-sourcing)
Number of digital outputs	8
Current-sourcing	Yes
Digital outputs, parameterizable	Yes
Short-circuit protection	Yes
<ul style="list-style-type: none"> <li>• Response threshold, typ.</li> </ul>	1 A
Limitation of inductive shutdown voltage to	Typ. L+ (-50 V)
Controlling a digital input	Yes
<b>Switching capacity of the outputs</b>	
<ul style="list-style-type: none"> <li>• with resistive load, max.</li> <li>• on lamp load, max.</li> </ul>	0.5 A 5 W
<b>Load resistance range</b>	
<ul style="list-style-type: none"> <li>• lower limit</li> <li>• upper limit</li> </ul>	48 Ω 12 kΩ
<b>Output voltage</b>	
<ul style="list-style-type: none"> <li>• for signal "1", min.</li> </ul>	L+ (-0.8 V)
<b>Output current</b>	
<ul style="list-style-type: none"> <li>• for signal "1" rated value</li> <li>• for signal "1" permissible range, max.</li> <li>• for signal "0" residual current, max.</li> </ul>	0.5 A 0.5 A 0.1 mA
<b>Output delay with resistive load</b>	
<ul style="list-style-type: none"> <li>• "0" to "1", max.</li> <li>• "1" to "0", max.</li> </ul>	50 μs; at rated load 100 μs; at rated load
<b>Parallel switching of two outputs</b>	
<ul style="list-style-type: none"> <li>• for uprating</li> <li>• for redundant control of a load</li> </ul>	No Yes
<b>Switching frequency</b>	
<ul style="list-style-type: none"> <li>• with resistive load, max.</li> <li>• with inductive load, max.</li> <li>• on lamp load, max.</li> </ul>	100 Hz 2 Hz 10 Hz
<b>Total current of the outputs</b>	
<ul style="list-style-type: none"> <li>• Current per channel, max.</li> <li>• Current per module, max.</li> </ul>	0.5 A 4 A
<b>Total current of the outputs (per module)</b>	
horizontal installation	
— up to 60 °C, max.	4 A
vertical installation	
— up to 50 °C, max.	4 A
<b>Cable length</b>	
<ul style="list-style-type: none"> <li>• shielded, max.</li> <li>• unshielded, max.</li> </ul>	1 000 m 600 m
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	Yes
Substitute values connectable	Yes
<b>Alarms</b>	
<ul style="list-style-type: none"> <li>• Diagnostic alarm</li> </ul>	Yes
<b>Diagnoses</b>	
<ul style="list-style-type: none"> <li>• Monitoring the supply voltage</li> <li>• Wire-break</li> <li>• Short-circuit to M</li> <li>• Short-circuit to L+</li> <li>• Group error</li> </ul>	Yes Yes; Module-wise Yes; Module-wise Yes; Module-wise Yes
<b>Diagnostics indication LED</b>	
<ul style="list-style-type: none"> <li>• Monitoring of the supply voltage (PWR-LED)</li> <li>• Channel status display</li> </ul>	Yes; green PWR LED Yes; green LED

<ul style="list-style-type: none"> <li>• for channel diagnostics</li> <li>• for module diagnostics</li> </ul>	No Yes; green/red DIAG LED		
<b>Potential separation</b>			
Potential separation channels			
<ul style="list-style-type: none"> <li>• between the channels</li> <li>• between the channels and backplane bus</li> <li>• between the channels and the power supply of the electronics</li> </ul>	No Yes No		
<b>Isolation</b>			
Isolation tested with	707 V DC (type test)		
<b>Standards, approvals, certificates</b>			
Suitable for safety functions	No		
Suitable for safety-related tripping of standard modules	Yes; see FAQ Entry ID: 39198632		
<b>Ecological footprint</b>			
<ul style="list-style-type: none"> <li>• environmental product declaration</li> </ul>	Yes		
<b>Global warming potential</b>			
— global warming potential, (total) [CO2 eq]	20.4 kg		
— global warming potential, (during production) [CO2 eq]	3.16 kg		
— global warming potential, (during operation) [CO2 eq]	17.5 kg		
— global warming potential, (after end of life cycle) [CO2 eq]	-0.221 kg		
<b>Highest safety class achievable in safety mode</b>			
<ul style="list-style-type: none"> <li>• Performance level according to ISO 13849-1</li> <li>• SIL acc. to IEC 61508</li> </ul>	PL d SIL 2		
<b>Ambient conditions</b>			
Ambient temperature during operation			
<ul style="list-style-type: none"> <li>• horizontal installation, min.</li> <li>• horizontal installation, max.</li> <li>• vertical installation, min.</li> <li>• vertical installation, max.</li> </ul>	-30 °C; < 0 °C as of FS02 60 °C -30 °C; < 0 °C as of FS02 50 °C		
Altitude during operation relating to sea level			
<ul style="list-style-type: none"> <li>• Installation altitude above sea level, max.</li> </ul>	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual		
<b>Dimensions</b>			
Width	15 mm		
Height	73 mm		
Depth	58 mm		
<b>Weights</b>			
Weight, approx.	30 g		
<b>Classifications</b>			
		<b>Version</b>	<b>Classification</b>
	eClass	14	27-24-26-04
	eClass	12	27-24-26-04
	eClass	9.1	27-24-26-04
	eClass	9	27-24-26-04
	eClass	8	27-24-26-04
	eClass	7.1	27-24-26-04
	eClass	6	27-24-26-04
	ETIM	9	EC001599
	ETIM	8	EC001599
	ETIM	7	EC001599
	IDEA	4	3566
	UNSPSC	15	32-15-17-05
<b>Approvals / Certificates</b>			
<b>General Product Approval</b>			



[Manufacturer Declaration](#)

[KC](#)



[KC](#)

General Product Approval | EMV | For use in hazardous locations



[KC](#)



[EM](#)

[CCC-Ex](#)



For use in hazardous locations | Marine / Shipping



[Miscellaneous](#)



Marine / Shipping | Environment

[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)



last modified:

10/9/2024